





CP3L2.5



3 Level Terminal Block
Jumper Channel Each Level

CP3L2.5(I.S)





3 Level Terminal Block
Internally Shorted

CP3LG2.5



3 Level Terminal Block
Bottom Ground

CP3LG2.5(I.S)



3 Level Terminal Block
6 Connections, Ground

Dimensions & Weight

| Width / Length | 5 mm / 98.70 mm | | 5 mm / 98.70 mm | | 5 mm / 98.70 mm | | 5 mm / 98.70 mm | |
|-------------------|-----------------|----------|-----------------|----------|-----------------|----------|-----------------|----------|
| Height w DIN Rail | 35 x 7.5 mm | 83.10 mm | 83.10 mm | 83.10 mm | 83.10 mm | 83.10 mm | 83.10 mm | 83.10 mm |
| | 35 x 15 mm | 90.60 mm | 90.60 mm | 90.60 mm | 90.60 mm | 90.60 mm | 90.60 mm | 90.60 mm |
| Weight per piece | 18.6 g | | 19.9 g | | 23.2 g | | 24.4 g | |

Technical Data/Ratings

| Approvals | | | | | | | | |
|------------------------------|------------------|--------------------------|------------------|--------------------------|---------------------|--------------------------|------------------|--------------------------|
| Wire Size (solid / stranded) | 22-12 AWG | 0.34-2.5 mm ² | 22-12 AWG | 0.34-2.5 mm ² | 22-12 AWG | 0.34-2.5 mm ² | 22-12 AWG | 0.34-2.5 mm ² |
| Voltage Rating | 300 V | 500V | 300 V | 500V | 300 V | 500V | 300 V | 500V |
| Current Rating | 20 A | 24 A | 20 A | 24 A | 20 A (Top 2 Levels) | 24 A (Top 2 Levels) | - | - |
| Insulation Material | Polyamide 66 | | Polyamide 66 | | Polyamide 66 | | Polyamide 66 | |

Installation Instructions



| | | | | | | | | |
|-----------------------|---------------------------------|--|---------------------------------|--|---------------------------------|--|---------------------------------|--|
| Wire Stripping Length | 10 mm | | 10 mm | | 10 mm | | 10 mm | |
| Screwdriver | SCM0.5/3.0 (0.5 x 3.0 mm blade) | | SCM0.5/3.0 (0.5 x 3.0 mm blade) | | SCM0.5/3.0 (0.5 x 3.0 mm blade) | | SCM0.5/3.0 (0.5 x 3.0 mm blade) | |

| Terminal Blocks | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. |
|------------------------|----------------|----------|---------------------|----------|-----------------|----------|----------------------|----------|
| Grey (standard) | CP3L2.5 | 30 | CP3L2.5(I.S) | 30 | - | - | - | - |
| Ground/ Earth | - | - | - | - | CP3LG2.5 | 30 | CP3LG2.5(I.S) | 30 |
| Yellow / Green | - | - | - | - | - | - | - | - |

| Jumpers | Cat. No. | Imax | Std. Pk. | Cat. No. | Imax | Std. Pk. | Cat. No. | Imax | Std. Pk. | Cat. No. | Imax | Std. Pk. | |
|------------------------|----------|-----------|----------|----------|-----------|----------|----------|-----------|----------|----------|-----------|----------|-----|
| Shorting Link/ Jumpers | 2 pole | CA801/A2 | 24A | 100 | CA801/A2 | 24A | 100 | CA801/A2 | 24A | 100 | CA801/A2 | 24A | 100 |
| | 3 pole | CA801/A3 | 24A | 100 | CA801/A3 | 24A | 100 | CA801/A3 | 24A | 100 | CA801/A3 | 24A | 100 |
| | 4 pole | CA801/A4 | 24A | 100 | CA801/A4 | 24A | 100 | CA801/A4 | 24A | 100 | CA801/A4 | 24A | 100 |
| | 10 pole | CA801/A10 | 24A | 10 | CA801/A10 | 24A | 10 | CA801/A10 | 24A | 10 | CA801/A10 | 24A | 10 |

| Accessories | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. |
|-------------|---------------|------------------|---------------|------------------|---------------|------------------|---------------|------------------|
| End Plate | EPCP3L2.5 | 30 | EPCP3L2.5 | 30 | EPCP3L2.5 | 30 | EPCP3L2.5 | 30 |
| DIN Rail | 2511120 | 20 | 2511120 | 20 | 2511120 | 20 | 2511120 | 20 |
| | CA701-15/S | 20 | CA701-15/S | 20 | CA701-15/S | 20 | CA701-15/S | 20 |
| End Stop | CA202 / CA103 | 50 | CA202 / CA103 | 50 | CA202 / CA103 | 50 | CA202 / CA103 | 50 |
| Marking Tag | MT2G | 1 Pk. (100 tags) | MT2G | 1 Pk. (100 tags) | MT2G | 1 Pk. (100 tags) | MT2G | 1 Pk. (100 tags) |

CP4LG2.5



4 Level Terminal Block
Bottom Ground

Dimensions & Weight

| | | |
|-------------------|------------------------|----------|
| Width / Length | 5 mm / 118.6 mm | |
| Height w DIN Rail | 35 x 7.5 mm | 93 mm |
| | 35 x 15 mm | 100.50mm |
| Weight per piece | 26.5 g | |

Technical Data/Ratings

| | | |
|------------------------------|---------------------|--------------------------|
| Approvals | | |
| Wire Size (solid / stranded) | 22-12 AWG | 0.34-2.5 mm ² |
| Voltage Rating | 300 V | 500V |
| Current Rating | 20 A (Top 3 Levels) | 24 A (Top 3 Levels) |

| | |
|---------------------|--------------|
| Insulation Material | Polyamide 66 |
|---------------------|--------------|

Installation Instructions

| | |
|-----------------------|---------------------------------|
| Wire Stripping Length | 10 mm |
| Screwdriver | SCM0.4/2.5 (0.4 x 2.5 mm blade) |

| Terminal Blocks | Cat. No. | Std. Pk. |
|--|-----------------|----------|
| Ground/ Earth Yellow / Green | CP4LG2.5 | 30 |

| Jumpers | Cat. No. | Imax | Std. Pk. |
|----------------|----------|-----------|----------|
| Shorting Link/ | 2 pole | CA801/A2 | 24A 100 |
| Jumpers | 3 pole | CA801/A3 | 24A 100 |
| | 4 pole | CA801/A4 | 24A 100 |
| | 10 pole | CA801/A10 | 24A 10 |

| Accessories | Cat. No. | Std. Pk. |
|-------------|---------------|------------------|
| End Plate | EPCP4LG2.5 | 30 |
| DIN Rail | 2511120 | 20 |
| | CA701-15/S | 20 |
| End Stop | CA202 / CA103 | 50 |
| Marking Tag | MT2G | 1 Pk. (100 tags) |