



1 POLE
Standard Pack 12




UL Recognized
E137915

Rated Current (I _n)	Type/ Cat. No.
0.5A	1D05UR
1.0A	1D1UR
2.0A	1D2UR
3.0A	1D3UR
4.0A	1D4UR
5.0A	1D5UR
6.0A	1D6UR
8.0A	1D8UR
10A	1D6UR
12A	1D12UR
13A	1D13UR
15A	1D15UR
16A	1D16UR
20A	1D20UR
25A	1D25UR
30A	1D30UR
32A	1D32UR
40A	1D40UR
50A	1D50UR
60A	1D60UR
63A	1D63UR

Weight (per piece)


0.3A - 32A:
0.120 - 0.141 kg
0.265 - 0.311 lb

33A - 63A:
0.137 - 0.158 kg
0.302 - 0.348 lb



D Trip Characteristic

I_n = 0.3A - 10A rated current



Specifications

Voltage Rating	0.5-63A / 480Y/277V AC
Short Circuit Withstand Rating	0.5 - 10A (RC): 10 kA with no back-up fuse 12 - 63A (RC): 10 kA with UL-listed Class J back-up fuse; 5 kA with no back-up fuse
Calibration Temperature	30°C (86°F)
Ambient Temperature	-25°C to +70°C (-13°F to 158°F)
Storage Temperature	-40°C to +70°C (-40°F to 158°F)
Terminal Torque (min/max)	2 Nm (17.7 lb.in.) / 2.5Nm (22.2 lb.in)
Electrical Life	6,000 switching cycles ON/ OFF
Mechanical Life	10,000 switching cycles ON/ OFF
Vibration Resistance	> 15g according to DIN EN 60069-2-59 during a load with 1.05 x I _n
Resistance to mechanical shocks	25g @ 11ms
Degree of protection acc. IEC/EN 60529	IP20
Mounting Orientation	In any plane

Short Circuit Withstand Ratings for DSL7 Supplementary Protector

Trip Curve	Amp Range	Backup Protection	
		UL-Listed Class J Fuse up to 10kA	No Backup Fuse Required up to:
all	0.5 - 10A	70A	10kA
all	12 - 63A	4xRC*	5kA

*up to nearest rated current

D Trip Characteristic

I_n = 13A - 63A rated current

