

Abox Pro 350 – Polycarbonate – 252 x 252 mm (9.92 x 9.92 in.)

Standard Features

- **Protection Level:** IP66/IP67/IP69
- **Technical:** Knockout Sidewalls (M20/M25/M40/M50)
- **UL Recognized**
- **Enclosure Material:** Polycarbonate
- **Gasket Material:** Thermoplastic Elastomer
- **Color:** Light Gray or Black
- **Material Operating Temperature Range:** Polycarbonate
-35°C to 80°C (-31°F to 176°F)
- **Included Accessories:** (4) M40 Double Membrane Seals for 17-28mm Cables
Cover Retainer
- **Accessories:** See section below



Abox Pro

Ordering Information	Cat. No.	Color	Screw Terminal	Length	Dimensions mm (in)	Width	Height	Std. Pk.
Enclosure with terminals	435-420-01	gray	35/25 mm ² - 5 pole	252 mm (9.92 in)	252 mm (9.92 in)	120 mm (4.72 in)	120 mm (4.72 in)	1
Enclosure with terminals	435-020-01	black	35/25 mm ² - 5 pole	252 mm (9.92 in)	252 mm (9.92 in)	120 mm (4.72 in)	120 mm (4.72 in)	1
Enclosure - empty	435-400-01	gray	NA	252 mm (9.92 in)	252 mm (9.92 in)	120 mm (4.72 in)	120 mm (4.72 in)	1
Enclosure - empty	435-000-01	black	NA	252 mm (9.92 in)	252 mm (9.92 in)	120 mm (4.72 in)	120 mm (4.72 in)	1

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Mounting Plate	895-135-01	MPI350	1
DIN Rail TS 35 – 35x120 mm	895-335-01	TS35/202	1
Terminal (high-set)	896-435-01	35/25 mm ² - 5 pole, 125A/690V	1
Pole Mount Kit (60-170mm)	896-040-01	MABF215-1	1

