

Abox Pro 025 – Polycarbonate – 92 x 92 mm (3.62 x 3.62 in.)

Standard Features

- **Protection Level:** IP66/IP67/IP69
- **Technical:** Knockout Sidewalls (M16/M20)
- **UL Recognized**
- **Enclosure Material:** Polycarbonate
- **Gasket Material:** Thermoplastic Elastomer
- **Color:** Light Gray or Black
- **Material Operating Temperature Range:** Polycarbonate
-35°C to 80°C (-31°F to 176°F)
- **Included Accessories:** (4) M20 Double Membrane Seals for 7-13mm Cables
Cover Retainer
- **Accessories:** See section below



Abox Pro

Ordering Information	Cat. No.	Color	Push-In Terminal	Length	Dimensions mm (in)	Width	Height	Std. Pk.
Enclosure with terminals	402-420-01	gray	2.5 mm ² - 5 pole x 5	92 mm (3.62 in)	92 mm (3.62 in)	92 mm (3.62 in)	60 mm (2.36 in)	3
Enclosure with terminals	402-020-01	black	2.5 mm ² - 5 pole x 5	92 mm (3.62 in)	92 mm (3.62 in)	92 mm (3.62 in)	60 mm (2.36 in)	3
Enclosure - empty	402-400-01	gray	NA	92 mm (3.62 in)	92 mm (3.62 in)	92 mm (3.62 in)	60 mm (2.36 in)	3
Enclosure - empty	402-000-01	black	NA	92 mm (3.62 in)	92 mm (3.62 in)	92 mm (3.62 in)	60 mm (2.36 in)	3

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
DIN Rail TS15 - 15x61 mm	895-202-01	TS15/61	1
Pole Mount Kit (60-170mm)	896-010-01	MABF65-1	1
Terminal (base mount)	896-404-01	2.5/4 mm ² - 5 pole, 41A/690V	10

