


Standard Features

- **Protection Level:** IP66/IP67/IP69
- **Technical:** Knockout Sidewalls (M20/M32)
Integral Mounting Tabs
- **UL Recognized**
- **Enclosure Material:** Polycarbonate
- **Gasket Material:** Thermoplastic Elastomer
- **Color:** Light Gray
- **Material Operating Temperature Range:** Polycarbonate
-35°C to 80°C (-31°F to 176°F)
- **Included Accessories:** (4) M32 Double Membrane Seals for 13-21mm Cables
Cover Retainer
- **Accessories:** See section below



Abox Pro

Ordering Information	Cat. No.	Color	Screw Terminal	Length	Dimensions mm (in) Width	Height	Std. Pk.
Enclosure with terminals	406-421-01	gray	6 mm ² - 5 pole	127 mm (5.00 in)	127 mm (5.00 in)	75 mm (2.95 in)	2
Enclosure - empty	406-401-01	gray	NA	127 mm (5.00 in)	127 mm (5.00 in)	75 mm (2.95 in)	2

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Mounting Plate	895-106-01	MPI060	1
DIN Rail TS 35 – 35x95 mm	895-306-01	TS35/95	1
Terminal (high-set)	896-406-01	6 mm ² - 5 pole, 41A/690V	5
Pole Mount Kit (60-170mm)	896-020-01	MABF100-1	1

