

Abox Pro 100 – Polycarbonate – 152 x 152 mm (5.98 x 5.98 in.)

Standard Features

- **Protection Level:** IP66/IP67/IP69
- **Technical:** Knockout Sidewalls (M20/M25/M32)
- **UL Recognized**
- **Enclosure Material:** Polycarbonate
- **Gasket Material:** Thermoplastic Elastomer
- **Color:** Light Gray or Black
- **Material Operating Temperature Range:** Polycarbonate
-35°C to 80°C (-31°F to 176°F)
- **Included Accessories:** (4) M32 Double Membrane Seals for 13-21mm Cables
Cover Retainer
- **Accessories:** See section below



Abox Pro

Ordering Information	Cat. No.	Color	Screw Terminal	Length	Dimensions mm (in)	Width	Height	Std. Pk.
Enclosure with terminals	410-420-01	gray	10 mm ² - 5 pole	152 mm (5.98 in)	152 mm (5.98 in)	85 mm (3.35 in)	85 mm (3.35 in)	2
Enclosure with terminals	410-020-01	black	10 mm ² - 5 pole	152 mm (5.98 in)	152 mm (5.98 in)	85 mm (3.35 in)	85 mm (3.35 in)	2
Enclosure - empty	410-400-01	gray	NA	152 mm (5.98 in)	152 mm (5.98 in)	85 mm (3.35 in)	85 mm (3.35 in)	2
Enclosure - empty	410-000-01	black	NA	152 mm (5.98 in)	152 mm (5.98 in)	85 mm (3.35 in)	85 mm (3.35 in)	2

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Mounting Plate	895-110-01	MPI100	1
DIN Rail TS 35 – 35x120 mm	895-310-01	TS35/120	1
Terminal (high-set)	896-410-01	10 mm ² - 5 pole, 57A/690V	5
Pole Mount Kit (60-170mm)	896-020-01	MABF100-1	1

