

Standard Features

- **Protection Level:** IP55* / IP66**
- **Technical:** Knockout Sidewalls (M20/M25/M40/M50)
- **UL Recognized**
- **Enclosure Material:** Polypropylene
- **Gasket Material:** Thermoplastic Elastomer
- **Color:** Light Gray
- **Material Operating Temperature Range:** Polypropylene
-25°C to 55°C (-13°F to 131°F)
- **Included Accessories:** (4) M40 Entry Spouts for Cables 17-30mm
(1) M40 Sealing Plug
(1) Cover Retainer
- **Accessories:** See section below



* With Supplied Entry Spouts

**As Equipped or With Optional IP66 Cable Glands

Abox

Ordering Information	Cat. No.	Color	Screw Terminal	Length	Dimensions mm (in) Width	Height	Std. Pk.
Enclosure with terminals	825-420-01	gray	35/25 mm ² - 5 pole	252 mm (9.92 in)	202 mm (7.95 in)	120 mm (4.72 in)	1
Enclosure - empty	825-400-01	gray	NA	252 mm (9.92 in)	202 mm (7.95 in)	120 mm (4.72 in)	1

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Mounting Plate	895-125-01	MPI250	1
DIN Rail TS 35 – 35x202 mm	895-335-01	TS35/202	1
DIN Rail TS 35 – 35x137 mm	895-316-01	TS35/137	1
Terminal (high-set)	896-435-01	35/25 mm ² - 5 pole, 125A/690V	1
Vertical Pole Mount Kit (60-170mm)	896-031-01	MABF150-2	1
Transverse Pole Mount Kit (60-170mm)	896-040-01	MABF215-1	1

